

LR-66

ULTRA HIGH PERFORMANCE

The LR-66 ultra-high-performance all-season tire is specially designed for the driving enthusiast; delivering responsive handling, cornering stability, and traction.



The asymmetrical pattern provides performance tuned from the inside-to-outside. The higher density inner siping improves wet and light snow traction; while the outside provides excellent dry handling and cornering stability. Asymmetric tread patterns allow for cross-rotation to maximize tread life.

Wide circumferential grooves evacuate water more effectively to improve traction in wet conditions

45K

MILES LIMITED
TREAD WEAR

56

SIZES
16" TO 20"



ALL-SEASON

Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
205/45ZR16	XL	87W	9.60	23.20	8.10	1201@49	420AA	LC0140
205/50ZR16	SL	87W	9.60	24.10	8.40	1201@44	420AA	LC0150
225/50ZR16	SL	92W	9.60	24.90	9.20	1389@44	420AA	LC0160
195/55R16	SL	87V	9.60	24.40	7.90	1201@44	420AA	LC0170
205/55R16	SL	91V	9.60	24.90	8.40	1356@44	420AA	LC0180
215/55ZR16	XL	97W	9.60	25.30	8.90	1609@49	420AA	LC0190
225/55ZR16	XL	99W	9.60	25.70	9.20	1709@49	420AA	LC0200
205/60R16	SL	92V	9.60	25.70	8.20	1389@44	420AA	LC0210
215/60R16	SL	95H	9.60	26.10	8.70	1521@44	420AA	LC0220
225/60R16	SL	98V	9.60	26.60	9.00	1653@44	420AA	LC0230
235/60R16	SL	100H	9.60	27.10	9.40	1764@44	420AA	LC0240
205/65R16	SL	95H	9.60	26.50	8.20	1521@44	420AA	LC0250
205/40ZR17	XL	84W	9.60	23.50	8.30	1102@49	420AA	LC0260
245/40ZR17	XL	95W	9.60	24.70	9.80	1521@49	420AA	LC0270
205/45ZR17	XL	88W	9.60	24.30	8.10	1235@49	420AA	LC0280
215/45ZR17	XL	91W	9.60	24.60	8.40	1356@49	420AA	LC0290
225/45ZR17	XL	94W	9.60	25.00	8.90	1477@49	420AA	LC0300
235/45ZR17	XL	97W	9.60	25.40	9.30	1609@49	420AA	LC0310
245/45ZR17	XL	99W	9.60	25.70	9.60	1709@49	420AA	LC0320
205/50ZR17	XL	93W	9.60	25.10	8.40	1433@49	420AA	LC0330
215/50ZR17	XL	95W	9.60	25.50	8.90	1521@49	420AA	LC0340
225/50ZR17	XL	98W	9.60	25.90	9.20	1653@49	420AA	LC0350
235/50ZR17	XL	100W	9.60	26.30	9.60	1764@49	420AA	LC0360
215/55ZR17	XL	98W	9.60	26.30	8.90	1653@49	420AA	LC0370
225/55ZR17	XL	101W	9.60	26.80	9.20	1819@49	420AA	LC0380
235/55ZR17	XL	103W	9.60	27.20	9.60	1929@49	420AA	LC0390
215/65R17	SL	99H	9.80	28.00	8.70	1709 @44	420AA	LC0395
255/35ZR18	XL	94W	9.80	25.00	10.20	1477@49	420AA	LC0400
215/40ZR18	XL	89W	9.60	24.80	8.60	1279@49	420AA	LC0410
225/40ZR18	XL	92W	9.60	25.10	9.10	1389@49	420AA	LC0420



LP-16

ALL-SEASON TOURING

The LP-16 all-season touring tire is engineered for small to midsize vehicles offering drivers a quiet and comfortable ride with excellent handling.



Optimized pitch sequence reduces tread pattern noise for a quiet ride.

Wide circumferential grooves and siping improves traction in wet and light snow conditions.

60K

MILES LIMITED
TREAD WEAR

22

SIZES
13" TO 16"



ALL-SEASON

Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
195/50R15	SL	82V	9.60	22.70	7.90	1047@44	560AA	LC0010
185/55R15	SL	82V	9.60	23.00	7.60	1047@44	560AA	LC0020
195/55R15	SL	85V	9.60	23.40	7.90	1135@44	560AA	LC0030
185/60R15	XL	88H	9.60	23.70	7.40	1235@49	560AA	LC0040
195/60R15	SL	88V	9.60	24.20	7.90	1235@44	560AA	LC0050
205/60R15	SL	91V	9.60	24.70	8.20	1356@44	560AA	LC0060
175/65R15	SL	84H	9.60	24.00	7.00	1102@44	560AA	LC0070
185/65R15	SL	88H	9.60	24.40	7.40	1235@44	560AA	LC0080
195/65R15	SL	91V	9.60	25.00	7.90	1356@44	560AA	LC0090
205/65R15	SL	94H	10.10	25.50	8.20	1477@44	560AA	LC0100
215/65R15	XL	100H	10.10	26.00	8.70	1764@49	560AA	LC0110
205/70R15	SL	96H	10.10	26.30	8.20	1565@44	560AA	LC0120
215/70R15	SL	98T	10.10	26.90	8.70	1653@44	560AA	LC0130
225/70R15	SL	100T	10.10	27.40	9.00	1764 @44	560AA	LC0132
195/50R16	SL	84V	9.60	23.70	7.90	1102 @44	560AA	LC0134
185/55R16	SL	83V	9.60	24.00	7.60	1074 @44	560AA	LC0136
225/65R16	SL	100H	10.10	27.50	9.00	1764 @44	560AA	LC0138
175/70R13		82T	9.57	22.70	7.00	1047@44	560AA	LC0002
175/65R14		82H	9.57	23.00	7.00	1047@44	560AA	LC0006
185/65R14		86H	9.57	23.50	7.40	1168@44	560AA	LC0007
185/70R14		88T	9.57	24.30	7.40	1235@44	560AA	LC0008



LX-01

SPORT TRUCK

The LX-01 sport truck tire is designed with an asymmetric tread pattern to provide exceptional handling and stability for the larger fitment sizes



Optimized pitch sequence reduces tread pattern noise for a quiet ride.

Large shoulder elements provide tire stability and enhanced control when cornering.

40K

MILES LIMITED
TREAD WEAR

22

SIZES
13" TO 16"



ALL-SEASON

Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
195/50R15	SL	82V	9.60	22.70	7.90	1047@44	560AA	LC0010
185/55R15	SL	82V	9.60	23.00	7.60	1047@44	560AA	LC0020
195/55R15	SL	85V	9.60	23.40	7.90	1135@44	560AA	LC0030
185/60R15	XL	88H	9.60	23.70	7.40	1235@49	560AA	LC0040
195/60R15	SL	88V	9.60	24.20	7.90	1235@44	560AA	LC0050
205/60R15	SL	91V	9.60	24.70	8.20	1356@44	560AA	LC0060
175/65R15	SL	84H	9.60	24.00	7.00	1102@44	560AA	LC0070
185/65R15	SL	88H	9.60	24.40	7.40	1235@44	560AA	LC0080
195/65R15	SL	91V	9.60	25.00	7.90	1356@44	560AA	LC0090
205/65R15	SL	94H	10.10	25.50	8.20	1477@44	560AA	LC0100
215/65R15	XL	100H	10.10	26.00	8.70	1764@49	560AA	LC0110
205/70R15	SL	96H	10.10	26.30	8.20	1565@44	560AA	LC0120
215/70R15	SL	98T	10.10	26.90	8.70	1653@44	560AA	LC0130
225/70R15	SL	100T	10.10	27.40	9.00	1764 @44	560AA	LC0132
195/50R16	SL	84V	9.60	23.70	7.90	1102 @44	560AA	LC0134
185/55R16	SL	83V	9.60	24.00	7.60	1074 @44	560AA	LC0136
225/65R16	SL	100H	10.10	27.50	9.00	1764 @44	560AA	LC0138
175/70R13		82T	9.57	22.70	7.00	1047@44	560AA	LC0002
175/65R14		82H	9.57	23.00	7.00	1047@44	560AA	LC0006
185/65R14		86H	9.57	23.50	7.40	1168@44	560AA	LC0007
185/70R14		88T	9.57	24.30	7.40	1235@44	560AA	LC0008



LS-07_{H/T}

CROSSOVER & SPORT UTILITY

The LS-07 H/T crossover and sport utility all-season tire is engineered for small to midsize vehicles offering drivers a quiet and comfortable ride with excellent handling.

LANCASTER



Optimized pitch sequence reduces tread pattern noise for a quiet ride.

Large shoulder elements provide tire stability and enhanced control when cornering.

60K

MILES LIMITED
TREAD WEAR

50

SIZES
15" TO 20"



ALL-SEASON

Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
235/75R15	XL	109T	9.80	28.90	9.30	2271@49	480AA	LC0760
215/65R16	SL	98H	9.80	27.00	8.70	1653@44	480AA	LC0770
235/65R16	XL	107H	9.80	28.00	9.40	2149@49	480AA	LC0780
205/70R16	SL	97T	9.80	27.30	8.20	1609 @44	480AA	LC0788
215/70R16	SL	100H	9.80	27.90	8.70	1764@44	480AA	LC0790
225/70R16	SL	103T	9.80	28.40	9.00	1929@44	480AA	LC0800
235/70R16	SL	106T	9.80	29.00	9.40	2094@44	480AA	LC0810
245/70R16	XL	111T	9.80	29.50	9.80	2403@49	480AA	LC0820
255/70R16	SL	111H	10.10	30.10	10.20	2403@44	480AA	LC0830
265/70R16	SL	112T	10.10	30.60	10.70	2469@44	480AA	LC0840
215/60R17	SL	96V	9.80	27.20	8.70	1565@44	480AA	LC0850
225/60R17	SL	99V	9.80	27.60	9.00	1709@44	480AA	LC0860
235/60R17	SL	102H	9.80	28.10	9.40	1874@44	480AA	LC0870
215/65R17	SL	99H	9.80	28.00	8.70	1709 @44	480AA	LC0878
225/65R17	SL	102T	9.80	28.50	9.00	1874@44	480AA	LC0880
235/65R17	XL	108H	9.80	29.10	9.40	2205@49	480AA	LC0890
245/65R17	SL	107H	9.80	29.50	9.80	2149@44	480AA	LC0900
255/65R17	SL	110H	10.10	30.10	10.20	2337 @44	480AA	LC0902
265/65R17		112T	9.83	30.60	10.70	2469@44	480AA	LC0904
245/70R17	SL	110H	9.80	30.60	9.80	2337@44	480AA	LC0910
265/70R17	SL	115T	9.80	31.70	10.70	2679@44	480AA	LC0920
225/55R18	XL	102V	9.60	27.80	9.20	1874 @49	480AA	LC0928
235/55R18	XL	104V	9.80	28.10	9.60	1984@49	480AA	LC0930
255/55ZR18	XL	109W	9.80	29.00	10.40	2271@49	480AA	LC0940
225/60R18	XL	104V	9.83	28.60	9.00	1984@49	480AA	LC0949
235/60R18	XL	107V	9.80	29.10	9.40	2149@49	480AA	LC0950



LS-07_{H/T}

CROSSOVER & SPORT UTILITY

LANCASTER



Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
245/60R18		105H	9.83	29.60	9.80	2039@44	480AA	LC0955
255/60R18	SL	108H	9.80	30.00	10.20	2205 @44	480AA	LC0958
265/60R18	SL	110H	9.80	30.50	10.70	2337@44	480AA	LC0960
235/65R18	XL	110H	9.83	30.00	9.40	2337@49	480AA	LC0964
255/65R18		111H	9.83	31.10	10.20	2403@44	480AA	LC0966
265/65R18		114H	9.83	31.50	10.70	2601@44	480AA	LC0968
275/65R18	SL	116H	10.10	32.10	11.00	2756@44	480AA	LC0970
265/70R18	SL	116T	10.10	32.60	10.70	2756 @44	480AA	LC0972
255/50R20	XL	109V	9.83	30.10	10.40	2271@49	480AA	LC0975
235/55R20	XL	105V	9.60	30.20	9.60	2039 @49	480AA	LC0977
255/55R20	XL	110V	9.80	31.00	10.40	2337 @49	480AA	LC0978
275/55R20	XL	117H	9.80	31.90	11.20	2833@49	480AA	LC0980
275/60R20	SL	115T	9.80	33.00	11.00	2679@44	480AA	LC0990
LT225/75R16		115S	12.60	29.30	8.80	2680/2470@80	---	LC2020
LT235/85R16		120S	12.60	31.70	9.30	3042 /2778 @80	---	LC2022
LT245/75R17		121S	12.60	31.00	10.00	3195/2910@80	---	LC2060
275/50R22	XL	115H	9.80	32.90	11.20	2679@49	480AA	LC0995
255/70R18		113T	9.80	32.10	10.20	2535@44	480AA	LC0971
265/75R16		116T	9.80	31.70	10.50	2756@44	480AA	LC0844
235/45R19		95H	9.83	27.40	9.30	1521@44	480AA	LC0974
225/75R16		104T	9.83	29.30	8.80	1984@44	480AA	LC0842
LT245/70R17		119S	9.83	30.60	9.80	3000/2755@80	---	LC2055
LT265/70R18		124S	12.60	32.60	10.70	3525/3195@80	---	LC2075
245/60R20		107H	9.83	31.50	9.80	2149@44	480AA	LC0988



LS-37_{A/T}

SUV & LIGHT TRUCK ALL-TERRAIN

The LS-37 A/T is a purpose build tire designed for off-road terrains with excellent on-road manners available in both sport utility and light truck sizes.

LANCASTER



The specially designed tread pattern delivers excellent on-road and off-road all-terrain performance.

The zig-zag grooves provide added traction in mud, dirt, and other soft surface terrains.

45K

MILES LIMITED
TREAD WEAR

40

SIZES
15" TO 22"



ALL-SEASON

Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
235/70R16	SL	106T	13.00	29.00	9.40	2094@44	560AB	LC1000
255/70R16		111T	12.98	30.10	10.20	2403@44	560AB	LC1005
265/70R16	SL	112T	13.00	30.60	10.40	2469@44	560AB	LC1010
275/70R16	SL	114S	13.00	31.20	11.00	2601@44	560AB	LC1020
245/75R16	SL	111S	13.00	30.50	9.80	2403 @44	560AB	LC1023
245/65R17	XL	111T	12.98	29.50	9.80	2149@44	560AB	LC1025
255/65R17	SL	110T	13.00	30.10	10.20	2337 @44	560AB	LC1028
265/65R17	SL	112S	13.00	30.60	10.70	2469@44	560AB	LC1030
275/65R17	SL	115S	13.00	31.10	11.00	2679@44	560AB	LC1040
285/65R17	SL	116S	13.00	31.60	11.50	2756@44	560AB	LC1050
265/70R17		115T	12.98	31.70	10.70	2535@44	560AB	LC1055
265/40R18	XL	101H	13.00	26.30	10.70	1819@49	560AB	LC1060
255/50R18	XL	106H	13.00	28.10	10.40	2094@49	560AB	LC1070
265/60R18	SL	110T	13.00	30.50	10.70	2337 @44	560AB	LC1072
265/65R18	SL	114T	13.00	31.50	10.70	2601 @44	560AB	LC1074
265/70R18	SL	116T	13.00	32.60	10.70	2756 @44	560AB	LC1076
275/55R20	XL	117H	13.00	31.90	11.20	2833@49	560AB	LC1080
275/60R20	XL	116H	12.98	33.00	11.00	2756@49	560AB	LC1083
285/45R22	XL	114H	13.00	32.10	11.20	2601@49	560AB	LC1090
LT235/75R15		104S	16.00	28.90	9.30	1985/1820@50	---	LC1094
LT225/75R16		115S	16.00	29.50	8.80	2680/2470@80	---	LC1100
LT245/75R16		120S	16.00	30.50	9.80	3042/2778@80	---	LC1102
LT265/75R16		123S	16.00	31.70	10.50	3415/3085@80	---	LC1104
LT285/75R16		126S	16.00	32.80	11.30	3750/3415@80	---	LC1106
LT315/75R16		127R	16.00	34.60	12.30	3860/3525 @65	---	LC1107
LT265/70R17		121S	16.00	31.70	10.70	3195/2910@80	---	LC1108



LS-37_{A/T}

SUV & LIGHT TRUCK ALL-TERRAIN



Size	Load	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	UTQG	Stock #
LT285/70R17		121Q	16.00	33.00	10.70	3195/2910@80	---	LC1110
LT245/75R17		121S	16.00	31.70	9.80	3195/2910@80	---	LC1120
LT235/80R17		120S	16.00	31.80	9.30	3085/2835@80	---	LC1125
LT275/65R18		123S	16.00	32.30	11.00	3415/3085@80	---	LC1130
LT285/65R18		125S	16.00	32.60	11.50	3640/3305@80	---	LC1132
LT275/70R18		125S	16.00	33.40	11.00	3640/3305@80	---	LC1140
LT275/65R20		126S	16.00	34.10	11.00	3750/3415@80	---	LC1142
31X10.50R15LT		109S	16.00	30.50	10.60	2270@50	---	LC1144
33X12.50R15LT		108S	16.00	32.50	12.50	2205@35	---	LC1145
265/50R20	XL	111T	13.00	30.00	11.00	2403@49	560AB	LC1078
LT265/60R20		121S	16.00	32.50	10.70	3195/2910@80	---	LC1189
LT285/60R20		125S	16.00	33.50	11.50	3640/3305@80	---	LC1191
LT285/75R18		129S	16.00	34.80	11.30	4080/3750@80	---	LC1141
245/70R16		107T	12.98	29.50	9.80	2149@44	560AB	LC1001



LS-57_{R/T}

LIGHT TRUCK RUGGED-TERRAIN

The LS-57 R/T is engineered to conquer the rugged off-road adventures and bring you home with excellent on-road handling

The specially designed multi-angle tread blocks provide excellent off-road performance in mud, dirt, gravel, and other soft surfaces.

Integrated stone ejector ribs protect the carcass from stone drilling.

LANCASTER



Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	Stock #
LT315/70R17	126Q	17.00	34.40	12.70	3750 /3415 @65	LC1147
LT275/55R20	120S	17.00	31.90	11.20	3085 /2835 @80	LC1148
LT285/55R20	122Q	17.00	32.60	11.70	3305/3000@80	LC1150
33X12.50R17LT	120Q	17.00	32.80	12.50	3085@65	LC1160
35X12.50R17LT	121Q	17.00	34.80	12.50	3195@65	LC1170
33X12.50R18LT	118Q	17.00	32.80	12.50	2910@65	LC1180
35X12.50R18LT	123Q	17.00	34.80	12.50	3415@65	LC1190
33X12.50R20LT	114Q	17.00	32.80	12.50	2600@65	LC1200
35X12.50R20LT	121Q	17.00	34.80	12.50	3195@65	LC1210
35X12.50R20LT	125Q	17.00	34.80	12.50	3640@80	LC1212
33X12.50R22LT	109Q	17.00	32.80	12.50	2270@65	LC1220
35X12.50R22LT	117Q	17.00	34.80	12.50	2835@65	LC1230
35X12.50R22LT	121Q	17.00	34.80	12.50	3195@80	LC1231
37X13.50R24LT	124Q	17.00	36.50	13.60	3525@80	LC1232

40K

MILES LIMITED
TREAD WEAR

14

SIZES
17" TO 24"



ALL-SEASON



LS-67_{M/T}

LIGHT TRUCK MAX-TRACTION

The LS-67 M/T is made for consumers seeking the ultimate in off-road traction; whether it be mud, dirt, sand, gravel or rocks.

The highly aggressive dual (A/B) pitch pattern provides excellent off-road performance in mud, dirt, gravel, and other soft surfaces

Integrated stone ejector ribs protect the carcass from stone drilling.

LANCASTER



21

SIZES
15" TO 24"



ALL-SEASON

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	Stock #
LT265/75R16	123Q	19.50	31.70	10.50	3415 /3085 @80	LC1234
LT265/70R17	123Q	19.50	31.70	10.70	3415 /3085 @80	LC1238
LT285/70R17	121Q	19.50	33.00	11.50	3195/2910@80	LC1240
LT285/65R18	125Q	19.50	32.60	11.50	3640 /3305 @80	LC1242
LT285/55R20	122Q	19.50	32.60	11.70	3307/2998@80	LC1250
33X12.50R15LT	108Q	19.50	32.80	12.50	2205@35	LC1260
35X12.50R15LT	113Q	19.50	34.80	12.50	2535@35	LC1270
33X12.50R17LT	120Q	19.50	32.80	12.50	3085@65	LC1280
35X12.50R17LT	121Q	19.50	34.80	12.50	3195@65	LC1290
33X12.50R18LT	118Q	19.50	32.80	12.50	2910@65	LC1300
35X12.50R18LT	123Q	19.50	34.80	12.50	3415@65	LC1310
33X12.50R20LT	114Q	19.50	32.80	12.50	2600@65	LC1320
35X12.50R20LT	121Q	19.50	34.80	12.50	3195@65	LC1330
35X12.50R20LT	125Q	19.50	34.80	12.50	3640@80	LC1332
37X13.50R20LT	128Q	19.50	36.80	13.60	3970@80	LC1340
33X12.50R22LT	114Q	19.50	32.80	12.50	2600@80	LC1350
35X12.50R22LT	121Q	19.50	34.80	12.50	3195@80	LC1360
37X13.50R22LT	128Q	19.50	36.80	13.60	3970@80	LC1370
35X12.50R24LT	111Q	19.50	34.80	12.50	2405@65	LC1380
35X12.50R24LT	116Q	19.50	34.80	12.50	2755@80	LC1382
37X13.50R24LT	124Q	19.50	36.80	13.60	3525@80	LC1390



LS-68M/T

LIGHT TRUCK MAX-TRACTION

The LS-68 M/T is specially designed for consumers seeking excellent off-road performance; whether it be mud, dirt, sand, gravel or rocks.



The highly aggressive dual (A/B) pitch pattern maximizes off-road performance in mud, dirt, gravel, and other soft surfaces.

Integrated stone ejector ribs protect the carcass from stone drilling.

Scalloped shoulders and deep sidewall buttress provides additional biting edges for increased off-road traction.

4

SIZES
15" TO 17"



ALL-SEASON

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	Stock #
LT285/75R16	126Q	19.53	32.80	11.30	3750/3415@80	LC1620
LT315/75R16	127Q	19.53	34.60	12.30	3860/3525@65	LC1630
31X10.50R15LT	109Q	19.53	30.50	10.60	2270@50	LC1680
LT255/75R17	111R	19.53	32.30	10.00	2405/2205@50	LC1668



LC-78

LIGHT TRUCK MAX-TRACTION

The LC-78 is designed for the frequent starts, stops, winding turns on the urban and rural roads. Van owners can be confident on the reliable performance and durable longevity.

LANCASTER



Balanced 4-rib pattern provides confident response and handling.

Optimized profile shape and pitch sequence reduces tread pattern noise for a quiet ride.

Wide circumferential grooves and siping improves traction in wet and light snow conditions.

5

SIZES
15" TO 16"



ALL-SEASON

Size	LI/SR	Tread Depth	Overall Diameter	Section Width	Max Load @PS	Stock #
235/65R16C	115T	11.09	28.00	9.40	2680/2535@65	LC3100
235/65R16C	121R	11.10	28.00	9.40	1449@65	LC3110
185/60R15C	94T	11.09	23.70	7.40	1477/1389@54	LC3040
205/65R15C	102T	11.09	25.50	8.20	1874/1764@54	LC3045
195/75R16C	107R	11.09	27.50	7.70	2149/2039@69	LC3115

